



ARC P™

Product Data Sheet

Delivering Tomorrow's Fluid Technologies Today

Description

A diffusion control additive for the waterbase aphron fluid technologies.

ARC P™ is a plasterizing polymer for enhancing the shells structure of aphrons used in waterbase aphron fluid technologies. When used in conjunction with **ARC S™**, **ARC G™**, **ARC A™** and **ARC P™** the resultant aphrons show significant resistance to compression as well as improved sealing performance when compared to aphrons built with **ARC S™** alone.

Properties

Form:	Liquid
Color:	Yellow
Specific gravity	0.981 @ 68° F
pH (1% in water)	Not determined
Solubility	Insoluble

Application

ARC P™ is a full circulating system treatment additive.

Initial treatment of waterbase aphron fluid technologies with **ARC P™** is typically with 0.3 pounds per barrel. Once the system has stabilized additional **ARC P™** should be added at a 1.0 : 0.3 pounds per barrel ratio (**ARC S™** to **ARC P™**) until a 12 - 14 % by volume aphron concentration is achieved in the circulating system.

Advantages

ARC P™ is a multi-benefit additive.

- Enhanced waterbase aphron fluid sealing performance
- No negative effect on the waterbase aphron fluid rheology performance (LSRV)
- Sealing by the "Jamin effect"
- "Micro-environment" sealing
- No or very low solids content fluids
- Minimally invasive fluids
- Improved Loss Circulation Control
- No differential sticking
- Quality cement bonds
- Optimized well construction costs

Handling and Storage

* Refer to Material Safety Data Sheet . . .

See the Material Safety Data Sheet for more detailed information concerning storage, handling, transportation, disposal and safety requirements.

Packaging

Specialty packaging is available . . .

ARC P™ is packaged in a special 5.0 gallon plastic pail designed to protect the product from moisture.

Questions & Answers

ARC Fluid Technologies, LLC "Offering You Tomorrow's Solutions Today"

If you would like to know more about the ARC Aphron Fluid Technologies and how it can improve your well performance please contact us at:

ARC Fluid Technologies, LLC
P.O. Box 130604
Spring, Texas
USA 77393-0604
Tel: +1-713-589-4877
Fax: +1-713-589-2375
E-mail: arcsolutions@arcfluids.com
Web: www.arcfluids.com

No claim of personal safety is intended nor implied by the use of the name Safe in this product. Personnel handling this material should read and follow all safety and handling procedures set forth on the Material Safety Data Sheet.